
FLEX™ Power Pak Control Panel

Single Phase Duplex, Type 4X (Indoor/Outdoor)
Model: FLXPO1D230 | 120/240VAC; 1-7A or 7-15A
OPAQUE DOOR, ALARM BEACON, and LOCKABLE LATCH

Alderon™ INDUSTRIES

MARKETING DATA FLIER



Panel Options (customize application)

- Control Circuit Breaker
- Current Sensors (displays and monitors Amps)
- Vizzy.Site™ Remote Monitoring

Scan the QR code in the ordering information section below or check our website configurator for Vizzylink™ hardware options.

STANDARD FEATURES

- **Type 4X Enclosure, Indoor or Outdoor, Pad-lockable**
  - Enclosure Size 10" x 8" x 4" (inches)
  - Opaque Door, Alarm Beacon with Red Flashing LEDs
  - Inner Door, View OLED Screen with Alarm and Status Indicator LEDs
  - Alarm Buzzer and Alarm Test/Silence Switch
- **Pump Circuit Breakers and Double-Pole Pump Relay Starters**
  - Pump Circuit Breakers for Pump Disconnect
- **Vibrant Multi-Color LEDs *(select indicators listed)***
  - Green (normal), Red (alarms), Blue (pump run), and Red/Yellow (error)
- **Automatic Resettable Alarm and Control Fuses**
- **Built-in Printed Circuit Board Surge Protection *(conformal coated)***
- **Easily Change Configurations**
  - Demand Dosing, Timed Dosing, Transducer Settings, Enable Pump Exerciser, and Seal Fail Alarm or Pump Shutdown
- **Sensor Options *(signaling device)***
  - Field Wire up to (5) Digital Inputs
  - Low Level Alarm and Auxiliary Switch Options
  - Configure 5th Input for a Control Float Switch, Auxiliary Switch, or 4-20mA Submersible Transducer (with 316 stainless steel cable hanger)
- **Statistic Tracking *(each pump)***
  - Pump Elapsed Time, Min/Max/Avg Pump Run Times, Pump Cycle Counter, Total Gallons Pumped, High Level Stats, and More
- **Included Auxiliary "Dry" Contacts**
  - General Alarm
  - Configurable Reverse Operated for General Alarm plus Power Loss
- **Hand-Off-Auto (HOA) Pump Selector Switch *(each pump)***
  - Off Reminder, Yellow Flashing LEDs and Displays "Pumps Disabled"
  - Configurable Pump Disable
- **Scroll Wheel and Digital Display *(password protected settings)***
  - Navigate Menu, Access Statistics Tracking, Configure Settings, and Displays System Information on OLED Screen
- **Exterior Test/Silence Switch**
  - Quick View of Pump and Alarm Stats, Alarm Test, or Silence Buzzer

ORDERING INFORMATION

Scan the QR code for more information on this product and website includes pricing.

FLEX™ POWER PAK - SINGLE PHASE | DUPLEX

Base Model	Control Panel Description
FLXPO1D230	FLEX™ Power Pak, Clear Door, Single Phase Duplex, 120/240VAC


Panel Code	Pump Full Load Amps (FLA)
R7	1.0 - 7.0 Amps
R15	7.0 - 15.0 Amps

Control Switch Options	Panel Code	Description (narrow angle models only)
Number of Control Switches	+3	(3) Control Switches
	+4	(4) Control Switches
Float Style	AG	Altra™ Gold Series
Activation Type *(Pump Down)*	H	High Level, Normally Open
Mounting Method (float attachment)	PS	Pipe Clamp, Stainless Steel
	WC	Cable Weight, Cast Iron
	WP	Cable Weight, Plastic
Cable Length (feet; standard)	20	20' Cable Length
	30	30' Cable Length
	50	50' Cable Length
	75	75' Cable Length
	100	100' Cable Length

***Example: FLXPO1D230R15+4AGHPS20** = FLEX™ Power Pak, Opaque Door, Single Phase Duplex, 120/240VAC, 7-15A, (4) 20' Control Switches, Stainless Steel Pipe Clamps*

FLEX™ Control Panel | PRODUCT DIMENSIONS and REMOTE MONITORING

Optionally connected to the Alderon™ cloud based Vizzy.Site™ for alarm and pump tracking statistics



ENCLOSURE SIZE	OVERALL Width (W)	OVERALL Height (H)	OVERALL Depth (D)	MOUNTING Width (M1)	MOUNTING Height (M2)
10 x 8 x 4	10.27	13.69	5.01	6.13	10.75

Enclosure measurements (inches)


OPTIONAL - REMOTE MONITORING

Vizzy.Site™ | 3 WAYS to CONNECT

1 ***WIFI***
Panel is connected where the WiFi signal is available AT the panel location ~ Panel Code: V1

2 ***ZIGBEE WIRELESS to WIRELESS WIFI***
Panel is connected up to 1,000 feet *(line of sight)* AWAY FROM where a WiFi signal is available from the panel location ~ Panel Code: V2

3 ***VERIZON CELLULAR***
Panel is connected as long as a Verizon cellular signal is available at the panel location ~ Panel Code: V3 (USA) and V4 (Canada)




MONITOR YOUR SYSTEM ANYWHERE with a SMARTPHONE, TABLET, or COMPUTER


When the product is connected to the Alderon™ Vizzy.Site™ cloud for remote monitoring; view product information for the device, configuration, event history, stats, alert rules, and information. Each tab includes additional information and selections to change system settings or view alarm and pump statistics.

Statistic examples include: System Pumping, Pump Run Stats, Pump Auxiliary Cutoff, Pump Overcurrent, Pump Undercurrent, Pump Seal Sensor Alarm, High Water Alarm, and Low Water Alarm (duplex; separate stats per pump).

Example: Pump 1 Overcurrent

PRESS the 'Clear Resettable' button to "reset" statistic to zero.
NOTE: Lifetime statistic values are NOT resettable





SUBSCRIPTIONS:

Options V1 and V2 | WiFi or Zigbee to WiFi

- VIZZY™ FREE - $0.00 | high or low level alarm monitoring only
- VIZZY™ PRO - $99.00/YEAR | full system monitoring of alarms and events, pump statistics, and more

Option V3 (USA) and V4 (Canada) | Cellular

- VIZZY™ PRO - $299.00/YEAR | full system monitoring of alarms and events, pump statistics, and more